

BCHZ0500C

General					
Refrigerant	Voltage	Compressor Type	Compressor Model	HP	Listings
R-404A	208-230/60/3	SEMI-HERM	2DC3-050E-TFC	5HP	UL/CUL
Capacity (Btu/h)					
At Room Temp. With a 10° TD, 90° Ambient					
-20	-10	0	30	35	40
				42078	46041
At Room Temp. With a 10° TD, 100° Ambient					
-20	-10	0	30	35	40
				38921	
At Room Temp. With a 10° TD, 110° Ambient					
-20	-10	0	30	35	40
				33975	

Dimensional Data				
Overall			Base Size	Base/Hood
L	W	H		
47	36	36	C	940/940

Installation				
Wt. Lbs.	Receiver Tank 90%/90°F	Connections Liquid	Suction	Refrigerant
600	41.5	5/8	1.375	R-404A

Electrical							
MCA	MOP	comp volts	comp phase	comp hz	comp RLA	comp LRA	other volts
34	50	208/230	3	60	22.3	120	208/230
fan phase	fan hz	fan FLA	fan HP	fan quantity	other load phase	other load amps	Approximate Sound Level (Db)
1	60	4.6	3/4	1	1	0.5	77

max evap fan amps	max evap def heater amps	Total Heat Rejection BTUH
0	0	53018

