

BCMZ0400C

| General | | | | | |
|---|--------------|-----------------|------------------|-------|----------|
| Refrigerant | Voltage | Compressor Type | Compressor Model | HP | Listings |
| R-404A | 208-230/60/3 | SEMI-HERM | NRB2-040E-TFC | 4HP | UL/CUL |
| Capacity (Btuh) | | | | | |
| At Room Temp. With a 10° TD, 90° Ambient | | | | | |
| -20 | -10 | 0 | 30 | 35 | 40 |
| | | | 32733 | 38900 | |
| At Room Temp. With a 10° TD, 100° Ambient | | | | | |
| -20 | -10 | 0 | 30 | 35 | 40 |
| | | | | 33909 | |
| At Room Temp. With a 10° TD, 110° Ambient | | | | | |
| -20 | -10 | 0 | 30 | 35 | 40 |
| | | | | 29006 | |

| Dimensional Data | | | | |
|------------------|----|----|-----------|-----------|
| Overall | | | Base Size | Base/Hood |
| L | W | H | | |
| 47 | 36 | 36 | C | 940/940 |

| Installation | | | | |
|--------------|------------------------|--------------------|---------|-------------|
| Wt. Lbs. | Receiver Tank 90%/90°F | Connections Liquid | Suction | Refrigerant |
| 530 | 41.5 | 5/8 | 1.125 | R-404A |

| Electrical | | | | | | | |
|-------------------|--------------------------|---------------------------|------------|--------------|------------------|-----------------|------------------------------|
| MCA | MOP | comp volts | comp phase | comp hz | comp RLA | comp LRA | other volts |
| 45 | 50 | 208/230 | 3 | 60 | 21.8 | 141 | 208/230 |
| fan phase | fan hz | fan FLA | fan HP | fan quantity | other load phase | other load amps | Approximate Sound Level (Db) |
| 1 | 60 | 2.9 | 1/3 | 1 | 1 | 0.5 | 0 |
| max evap fan amps | max evap def heater amps | Total Heat Rejection BTUH | | | | | |
| 7 | 35 | 41898 | | | | | |

