

**MCHZ0071C**

General					
Refrigerant	Voltage	Compressor Type	Compressor Model	HP	Listings
R-404A	208-230/60/3	SEMI-HERM	KANA-007E-TAC	.75HP	UL/CUL
Capacity (Btuh)					
At Room Temp. With a 10° TD, 90° Ambient					
-20	-10	0	30	35	40
			6270	6894	7518
At Room Temp. With a 10° TD, 100° Ambient					
-20	-10	0	30	35	40
				5398	
At Room Temp. With a 10° TD, 110° Ambient					
-20	-10	0	30	35	40
				4529	

Dimensional Data				
Overall			Base Size	Base/Hood
L	W	H		
22	27	18	M1	011M

Installation				
Wt. Lbs.	Receiver Tank 90%/90°F	Connections Liquid	Suction	Refrigerant
270	7.7	3/8	5/8	R-404A

Electrical							
MCA	MOP	comp volts	comp phase	comp hz	comp RLA	comp LRA	other volts
13	15	208-230	3	60	3.5	19.9	208/230
fan phase	fan hz	fan FLA	fan HP	fan quantity	other load phase	other load amps	Approximate Sound Level (Db)
1	60	0.5	1/20	1	1	0.5	65
max evap fan amps	max evap def heater amps	Total Heat Rejection BTUH					
3	10	8686					

