

MHHZ0111B

General					
Refrigerant	Voltage	Compressor Type	Compressor Model	HP	Listings
R-404A	208-230/60/1	HERMETIC	RS70C1E-PFV	1HP	UL/CUL
Capacity (Btuh)					
At Room Temp. With a 10° TD, 90° Ambient					
-20	-10	0	30	35	40
			8040	9080	10300
At Room Temp. With a 10° TD, 100° Ambient					
-20	-10	0	30	35	40
				7846	
At Room Temp. With a 10° TD, 110° Ambient					
-20	-10	0	30	35	40
				6484	

Dimensional Data				
Overall			Base Size	Base/Hood
L	W	H		
22	27	18	M1	011M

Installation				
Wt. Lbs.	Receiver Tank 90%/90°F	Connections Liquid	Suction	Refrigerant
250	7.7	3/8	7/8	R-404A

Electrical							
MCA	MOP	comp volts	comp phase	comp hz	comp RLA	comp LRA	other volts
20	20	208-230	1	60	7	34.2	208/230
fan phase	fan hz	fan FLA	fan HP	fan quantity	other load phase	other load amps	Approximate Sound Level (Db)
1	60	0.5	1/20	1	1	0.5	73
max evap fan amps	max evap def heater amps	Total Heat Rejection BTUH					
3	15	11441					

