

MSHZ0201B

General					
Refrigerant	Voltage	Compressor Type	Compressor Model	HP	Listings
R-404a	200-230/60/1	SCROLL	ZB15KCE-PFV	2HP	UL/CUL
Capacity (Btuh)					
At Room Temp. With a 10° TD, 90° Ambient					
-20	-10	0	30	35	40
			17312	18932	20530
At Room Temp. With a 10° TD, 100° Ambient					
-20	-10	0	30	35	40
				16400	
At Room Temp. With a 10° TD, 110° Ambient					
-20	-10	0	30	35	40
				14600	

Dimensional Data				
Overall			Base Size	Base/Hood
L	W	H		
38	27	18	M2	021M

Installation				
Wt. Lbs.	Receiver Tank 90%/90°F	Connections Liquid	Suction	Refrigerant
405	11.4	1/2	7/8	R-404a

Electrical							
MCA	MOP	comp volts	comp phase	comp hz	comp RLA	comp LRA	other volts
26	40	200/230	1	60	15.7	61	208/230
fan phase	fan hz	fan FLA	fan HP	fan quantity	other load phase	other load amps	Approximate Sound Level (Db)
1	60	0.5	1/20	2	1	0.5	73
max evap fan amps	max evap def heater amps	Total Heat Rejection BTUH					
5	15	23855					

