

MSHZ0201C

| General | | | | | |
|---|--------------|-----------------|------------------|-------|----------|
| Refrigerant | Voltage | Compressor Type | Compressor Model | HP | Listings |
| R-404a | 200-230/60/3 | SCROLL | ZB15KCE-TF5 | 2HP | UL/CUL |
| Capacity (Btuh) | | | | | |
| At Room Temp. With a 10° TD, 90° Ambient | | | | | |
| -20 | -10 | 0 | 30 | 35 | 40 |
| | | | 17182 | 18897 | 20577 |
| At Room Temp. With a 10° TD, 100° Ambient | | | | | |
| -20 | -10 | 0 | 30 | 35 | 40 |
| | | | | 16186 | |
| At Room Temp. With a 10° TD, 110° Ambient | | | | | |
| -20 | -10 | 0 | 30 | 35 | 40 |
| | | | | 14219 | |

| Dimensional Data | | | | |
|------------------|----|----|-----------|-----------|
| Overall | | | Base Size | Base/Hood |
| L | W | H | | |
| 38 | 27 | 18 | M2 | 021M |

| Installation | | | | |
|--------------|------------------------|--------------------|---------|-------------|
| Wt. Lbs. | Receiver Tank 90%/90°F | Connections Liquid | Suction | Refrigerant |
| 405 | 11.4 | 1/2 | 7/8 | R-404a |

| Electrical | | | | | | | |
|-------------------|--------------------------|---------------------------|------------|--------------|------------------|-----------------|------------------------------|
| MCA | MOP | comp volts | comp phase | comp hz | comp RLA | comp LRA | other volts |
| 19 | 25 | 200/230 | 3 | 60 | 8.9 | 55 | 208/230 |
| fan phase | fan hz | fan FLA | fan HP | fan quantity | other load phase | other load amps | Approximate Sound Level (Db) |
| 1 | 60 | 0.5 | 1/20 | 2 | 1 | 0.5 | 73 |
| max evap fan amps | max evap def heater amps | Total Heat Rejection BTUH | | | | | |
| 5 | 15 | 23810 | | | | | |

