

**MSHZ0301C**

General					
Refrigerant	Voltage	Compressor Type	Compressor Model	HP	Listings
R-404a	200-230/60/3	SCROLL	ZB21KCE-TF5	3HP	UL/CUL
Capacity (Btuh)					
At Room Temp. With a 10° TD, 90° Ambient					
-20	-10	0	30	35	40
			25647	28076	30475
At Room Temp. With a 10° TD, 100° Ambient					
-20	-10	0	30	35	40
				24463	
At Room Temp. With a 10° TD, 110° Ambient					
-20	-10	0	30	35	40
				21739	

Dimensional Data				
Overall			Base Size	Base/Hood
L	W	H		
30	31	26	M3	031M

Installation				
Wt. Lbs.	Receiver Tank 90%/90°F	Connections Liquid	Suction	Refrigerant
405	15.2	5/8	7/8	R-404a

Electrical							
MCA	MOP	comp volts	comp phase	comp hz	comp RLA	comp LRA	other volts
26	35	200/230	3	60	12.1	77	208/230
fan phase	fan hz	fan FLA	fan HP	fan quantity	other load phase	other load amps	Approximate Sound Level (Db)
1	60	1.6	1/4	1	1	0.5	73
max evap fan amps	max evap def heater amps	Total Heat Rejection BTUH					
7	20	35376					

